

Pneumatic volumetric filling unit for liquid, semi-thick and pasty products



OEM	G.S. ITALIA
Model	GR-T
Country of origin	Italy



Description:

Easy to use, these filling units are ideal for small and medium productions for the preparation of samples or for laboratory. They are available in different models and with different optionals. Capacity from GR. 35 - 70 - 170 - 300 - 500 to 1000.

- Installed on a stainless steel base at floor with 4 wheels (2 with brakes)
- Adjustable filling capacity: up to max. 500 cc. by means of a threaded wheel with reference to graduated scale
- Operation: Manual by pedal and/or Automatic operation
- Standard stainless steel conic hopper, polished inside - volume 30 l. (other volumes upon request)
- Dosing cylinder made of lapped stainless steel
- Stainless steel dosing piston
- Special rulon joints, suitable for foodstuffs: non-toxic joints made of special material for a long life and high resistance up to max. product temperature 100°C
- Stroke-end: special microswitches that allow to work at high speeds with absolute and constant filling accuracy due to the fact that product is filled only when piston has totally accomplished its course.
- Pneumatic installation: for filling unit operation it's necessary only compressed air at 6 ATM - consumption about 190 NL/min. There is no need of lubrication because its components are self-lubricating.
- Table-Filler models: 50 - 70 - 100 - 170 - 200 and 300GR. are manufactured in "SM" version - i.e. quickly and easily disassembled (without tools) for cleaning and maintenance operations, thanks

www.altrapack.ru

Sales

T/ф: +7 (499) 397 7038

E-mail: altrapack@altrapack.ru

Service

T/ф: +7 (499) 397 7038

E-mail: service@altrapack.ru

to rapid CLAMP connections.
